

## DESSICANT DRYER

Heatless Type  
Heater Type  
Zero Purge Type  
Up to 50 Bar



### Dessicant Dryer Specification

Model	F-1	F-2	F-3	F-6	F-8	F-10	F-13	F-15	F-20
Capacity Nm <sup>3</sup> /min (cfm)	1.2(42)	2.4(85)	3.8(132)	6.5(230)	8(280)	11(388)	11(388)	17(600)	22(800)
Connection (inch)	1	1	1.5	1.5	2	2	2	3	3
Weight (kg)	180	240	350	510	550	780	780	900	1280
Dimension (L x W x H) mm	689x670x1298	690x670x1678	779x570x1498	900x800x1741	984x850x1895	1084x890x1805	1084x890x2015	1288x1050x1908	1288x1050x2217
Model	F-25	F-30	F-40	F-50	F-60	F-80	F-100	F-150	F-200
Capacity Nm <sup>3</sup> /min (cfm)	27(950)	32(1250)	42(1480)	55(1950)	65(2280)	85(2980)	110(3850)	150(5300)	200(7070)
Connection (inch)	3	3	4	5	5	5	6	8	10
Weight (kg)	1520	1760	2200	2600	3100	4100	5200	6000	6800
Dimension (L x W x H) mm	1412x1110x2241	1513x1150x2218	1652x1310x2403	1815x800x2473	1815x800x2473	2013x900x2570	2300x1500x2933	2700x1800x3429	2900x2000x3529
Dew Point	-40°C/-70°C								
Power	220V/1P/50Hz								