

AIR DRYER

High inlet temperature (80°C),
With double cooler, most compatible
For tropical high daily temperature climate like Indonesia.
Up to 50 Bar



Air Dryer Specification

Model	EAD 10A	EAD 20A	EAD 30A	EAD 50A	EAD 75A	EAD 100A	EAD 150A	EAD 250A	EAD 300A
Capacity (m ³ /min)	1.4	2.7	4.3	7.2	11	15	22	25	30
Inlet Temperature	55°C (max : 80°C)								
Working Pressure	10 Bar								
Refrigerant	R410A					R407c			
Power Supply	1 PH 220v 50Hz				3 PH 380v 50Hz				
Compressor Power (kW)	0.375	0.563	0.75	1.125	1.875	2.25	3	3.75	4.25
Connection	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3"	3"	3"
Wight (kg)	68	90	120	128	198	253	268	287	360
Dimension L x W x H (mm)	700x470x770	800x470x820	860x500x1100	920x520x1140	1200x600x1140	1200x620x1170	1200x620x1170	1320x650x1240	1700x900x1580

Model	EAD 350A	EAD 450A	EAD 550A	EAD 650A	EAD 750A	EAD 850A	EAD 1000A	EAD 1200A	EAD 1300A
Capacity (m ³ /min)	35	45	55	65	75	85	100	120	130
Inlet Temperature	55°C (max : 80°C)								
Working Pressure	10 Bar								
Refrigerant	R407c								
Power Supply	3 PH 380v 50Hz								
Compressor Power (kW)	6	10	12	13	14	15	17	19	21
Connection	4"	5"	5"	5"	5"	5"	5"	6"	6"
Wight (kg)	520	520	730	820	850	870	980	1120	1160
Dimension L x W x H (mm)	1700x960x1660	1800x960x1660	1900x1200x1400	2200x1150x1600	2200x1150x1600	2500x1380x1950	2650x1380x2070	2650x1380x2070	2800x1500x1930