

ZS SERIES COMPRESSOR

Special Design For Laser Cutting
Easy Installation
Low Noise



All In One Laser Cutting Compressor Specification

Model	ZS8A	ZS11A	ZS15A	ZS22A
Free air deliver/Discharge pressure (m³/min/Mpa)	0.48/1.6	0.8/1.6	1.25/1.6	1.75
Compression Stage	Single Stage			
Ambient Temperature	-5--+45°C			
Cooling Mode	Air-Cooling			
Discharge Temperature (°C)	Ambient Temperature+15°C			
Lubricant (L)	3.7	10	10	10
Noise Level (Db)	62±2	64±2	64±2	64±2
Drive Method	Belt Driven			
Electricity (V/ph/Hz)	380/3/50			
Motor Power (KW/HP)	7.5/10	11/15	15/20	22/30
Starting Method	Direct Starting	Y-ΔStarter (Star delta starting)		
Dimension L*W*H (mm)	1900x700x1630	1900x700x1630	2000x800x1800	2200x1000x2000
Net Weight (kg)	425	475	540	600
Air Outlet Diameter (inch/mm)	3/4"	3/4"	3/4"	1"

MICRON FILTER

Micron Filter Specification

Model	BL- 015	BL- 024	BL- 035	BL- 060	BL- 90	BL- 120	BL- 150
Hp	10- 15Hp	20	30	50	75	100	125- 150
Inch	1"	1"	1"	1-1/2"	2"	2"	2 1/2"
Capacity	2.1	2.7	4.3	7.2	11.0	15.0	21.0

