

# AIR DRYER

High Inlet Temperature (80°C)  
With Double Cooler, Most Compatible  
For Tropical High Daily Temperature Climate Like Indonesia  
Up to 50 Bar



## Air Dryer Specification

Model	EAD 10A	EAD 20A	EAD 30A	EAD 50A	EAD 75A	EAD 100A	EAD 150A	EAD 250A	EAD 300A
Capacity (m <sup>3</sup> /min)	1.4	2.7	4.3	7.2	11	15	22	25	30
Inlet Temperature	55°C (max : 80°C)								
Working Pressure	10 Bar								
Refrigerant	R410A					R407c			
Power Supply	1 PH 220v 50Hz				3 PH 380v 50Hz				
Compressor Power (kW)	0.375	0.563	0.75	1.125	1.875	2.25	3	4.5	5.3
Connection	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3"	3"	4"
Wight (kg)	68	90	120	128	198	253	268	428	510
Dimension L x W x H (mm)	700x470x770	800x470x820	860x500x1100	920x520x1140	1200x600x1140	1200x620x1170	1200x620x1170	1650x800x1600	1650x800x1600

Model	EAD 350A	EAD 450A	EAD 550A	EAD 650A	EAD 750A	EAD 850A	EAD 1100A	EAD 1200A	EAD 1300A
Capacity (m <sup>3</sup> /min)	35	45	55	65	75	85	110	120	130
Inlet Temperature	55°C (max : 80°C)								
Working Pressure	10 Bar								
Refrigerant	R407c								
Power Supply	3 PH 380v 50Hz								
Compressor Power (kW)	6	7.5	9	9.8	11.2	15	18.7	22.5	22.5
Connection	4"	4"	5"	5"	5"	6"	6"	6"	6"
Wight (kg)	750	900	910	1100	1120	1250	1300	1400	1500
Dimension L x W x H (mm)	1880x800x1650	2180x1180x1750	2180x1180x1750	2230x1220x1850	2230x1220x1850	2300x1280x2000	2400x1360x2100	2450x1400x2200	2450x1400x2200